



ZESTAWIENIE STAL ZBROJENOWEJ						
Poz.	Sila	Dlugosc A=mm	S mm ²	ciężar elementu ogloblego	Dlugosc (m)	
					A=mm	0.25
1	16	12000	408	408	0.12	0.16
2	12	4250	152	152	466.00	4988.00
3	22	3530	189	1	189	673.16
4	16	4195	505	1	505	2315.70
5	22	4680	189	1	189	1238.76
6	22	4680	189	1	189	507.65
7	12	6520	92	1	92	555.83
8	12	1950	152	1	152	298.40
9	12	3400	24	1	24	81.60
10	12	5550	24	1	24	13.30
11	12	1830	232	1	232	447.78
12	16	11450	186	1	186	2129.70
13	16	2240	93	1	93	223.20
14	16	2870	408	1	408	1170.95
15	16	1950	36	1	36	60.84
Dlugosc w zwichlu (m)				2202.86	3014.82	
Ciężar w zwichlu (kg/m)				0.89	1.58	2.48
Ciężar (kg/m)				16706.66	9071.56	
Ciężar (kg/m)				27735.45		

BETON:

- ZBIORNIK: C35/45
mrozoodporność: F-150
wodoszczelność: W-6
- BETON SPADKOWY: C30/37
- WASTWA OCHRONNA C8/10
- WASTWA WTRÓJNIAWCA C8/10

STAL ZBROJENIOWA: A-IIIIN

[illegible]